



Engine Oil mineral



10W30



15W40



20W50

General Description		
10W30	15W40	20W50
A premium engine oil for naturally aspirated and turbo charged petrol and LPG vehicles designed to aid in the reduction of fuel consumption and provide protection against engine wear in late design engines.	A high performance engine lubricant, designed to meet the requirements of a wide range of naturally aspirated and turbo charged petrol and light duty Diesel engines.	All season multi-grade heavy duty engine lubricant for naturally aspirated and turbo charged petrol, LPG and Diesel engines, designed to offer maximum protection against wear, corrosion and oxidation.
Benefits		
10W30	15W40	20W50
<ul style="list-style-type: none"> / Protection against sludge and deposits. / Resists viscosity and thermal breakdown. / Maintains viscosity grade. / Very high resistance against oxidation. / Recommended for Petrol, LPG and E10 fuelled engines. / Low loss by evaporation. 	<ul style="list-style-type: none"> / Very high resistance against oxidation. / High detergent and dispersing properties. / Very large application field. / Low loss by evaporation. / High performance in high and low temperature conditions. / Excellent protection against wear. / Recommended for Petrol, light Diesel, LPG and E10 fuelled engines. 	<ul style="list-style-type: none"> / Very high resistance against oxidation. / High detergent and dispersant properties. / Low loss by evaporation. / High performance in high and low temperature conditions. / Excellent protection against wear. / Recommended for Petrol, light Diesel, LPG and E10 fuelled engines. / Very large application field.

ACDelco offers a comprehensive Product Range to suit Most Makes & Models.

For your nearest ACDelco Automotive Parts Stockist call 1800 ACDelco

1800 ACDelco
acdelco.com.au

Suits Most Makes Most Models





Engine Oil mineral

Approvals and Performance Ratings		
10W30	15W40	20W50
Petrol powered engines that specify the use of a SAE 10W-30.	Mercedes-Benz MB229.1 This all seasons oil is especially recommended for mixed fleets (passenger cars and light commercial vehicles). It can be used in most services, in Diesel engines with natural aspiration or with turbo discharge and in most petrol engines.	Up-to-date 4-stroke Petrol engines (multi-valves, turbo, etc.). 4-stroke Diesel engines of passenger cars, with or without turbo.
Specifications		
10W30	15W40	20W50
API SM	API SM/CF	API SL/CF
ILSAC GF-3	ACEA A3/B3	
Container – Part Number		
10W30	15W40	20W50
1 Litre – 88900941	1 Litre – 88900930	1 Litre – 88900934
5 Litre – 88900942	5 Litre – 88900931	5 Litre – 88900935
20 Litre – 88900943	20 Litre – 88900932	20 Litre – 88900936
205 Litre – 88900944	205 Litre – 88900933	205 Litre – 88900937



1 Litre



5 Litre



20 Litre



205 Litre

For further details refer to the ACDelco website www.acdelco.com.au

Available
From:

ACD6521

1800 ACDelco
acdelco.com.au

Suits Most Makes Most Models

