



# Engine Oil

## synthetic / semi synthetic



5W30



5W40



10W30

General Description		
5W30	5W40	10W30
<p>This new ACDelco Supreme Plus 5W30 is a fully synthetic high performance C3 low SAPS engine oil – Suitable for use in normally aspirated and turbocharged petrol and light duty Diesel engines, such as fitted to the latest generation of Euro passenger cars, SUV's and light commercial vehicles where a low viscosity oil is required, especially when equipped with exhaust filter systems, catalyts or EGR systems.</p>	<p>A fully synthetic engine oil designed to offer maximum performance and protection under severe conditions for Australian and European vehicles applications in petrol and Diesel naturally aspirated and turbocharged vehicles.</p>	<p>The new ACDelco Supreme 10W30 Engine Oil is a high performance semi–synthetic engine oil for normally aspirated and turbocharged petrol and light duty Diesel engines, such as fitted to the late petrol and Diesel powered passenger cars, SUVs, and light commercial vehicles.</p>
Benefits		
5W30	5W40	10W30
<ul style="list-style-type: none"> <li>/ Provides protection of exhaust gas after treatment devices like particulate filters, CRT's or oxidation catalyts by its very low levels of sulphated ash, phosphorous and sulphur.</li> <li>/ Excellent protection against wear in the advanced highly stressed Diesel and petrol engines of today.</li> <li>/ Miscible (can be mixed) with other engine oils.</li> <li>/ Free flowing formulation reduces oiling time, improving wear protection and performance.</li> <li>/ Assists in preventing deposits in the engine and turbocharger to ensure full boost pressure, engine power and fuel economy are maintained.</li> <li>/ Resists oxidation and thermal breakdown even in severe service.</li> <li>/ Protection against sludge and deposits.</li> <li>/ Maintains viscosity grade.</li> </ul>	<ul style="list-style-type: none"> <li>/ Superior Wear Protection.</li> <li>/ Excellent Thermal and oxidation stability.</li> <li>/ Low volatility.</li> <li>/ Protects Against Sludging.</li> <li>/ Free flowing formulation reduces oiling time, improving wear protection and performance.</li> <li>/ Low phosphorous levels to assist the performance and life of catalytic converters.</li> <li>/ Excellent protection against wear in the advanced highly stressed Diesel and petrol engines of today.</li> </ul>	<ul style="list-style-type: none"> <li>/ Stay–in–grade lubricant maintains its wear protection.</li> <li>/ Provides superior performance compared to ILSAC GF–3 and API SL lubricants.</li> <li>/ Synthetic base oil minimises oil consumption due to low evaporation.</li> <li>/ Protects against oil slugging of engine components.</li> <li>/ Lower phosphorus level to reduce catalytic converter blockages.</li> <li>/ Minimises loss of performance as a result of unwanted deposits.</li> <li>/ Miscible (can be mixed) with all mineral oil and synthetic oil – No flushing is required.</li> <li>/ Very high resistance against oxidation.</li> <li>/ Recommended for Petrol, Diesel, LPG and E10 fuelled engines.</li> <li>/ Low loss by evaporation.</li> </ul>

**ACDelco offers a comprehensive Product Range to suit Most Makes & Models.**

*For your nearest ACDelco Automotive Parts Stockist call 1800 ACDelco*

1800 ACDelco  
acdelco.com.au

**Suits Most Makes Most Models**





# Engine Oil

## synthetic / semi synthetic

Approvals and Performance Ratings		
5W30	5W40	10W30
BMW Longlife-04. Mercedes-Benz 229.51 Renault VW specifications 502 00 / 505 00	BMW Longlife 98 Mercedes-Benz MB229.3 Porsche VW 502 00 / 505 00 / 505 01	Allows for the rationalisation of grades and containers in the workshop as it can also be used where the following SAE grades in mineral oil are specified: 5W40, 10W40, 15W40, 20W40, 20W30, 10W30, 5W30. To obtain the full benefits of this oil, please fully drain the system and refill with ACDelco Supreme 10W30 Semi-Synthetic Engine Oil.
Specifications		
5W30	5W40	10W30
API SM/CF	API SM/CF	API SM/CF
ACEA C3/A3/B4	ACEA A3/B3/B4	ILSAC GF-4
Container – Part Number		
5W30	5W40	10W30
5 Litre – 89063549	5 Litre – 89062649	1 Litre – 89063552
		5 Litre – 89063553
		20 Litre – 89063554
		205 Litre – 89063555



1 Litre



5 Litre



20 Litre



205 Litre

**For further details refer to the ACDelco website [www.acdelco.com.au](http://www.acdelco.com.au)**

Available From:

1800 ACDelco  
[acdelco.com.au](http://acdelco.com.au)

**Suits Most Makes Most Models**

