



SELECT 10W30 SM GF-3 – ENGINE OIL

PART NUMBERS:

1 Litre	88900941
5 Litre	88900942
20 Litre	88900943
205 Litre	88900944

MOTOR OIL FOR PETROL ENGINES

DESCRIPTION:

ACDelco Select SAE 10W-30 Motor Oil is a high quality mineral motor oil, suitable for use in 4-stroke naturally aspirated and turbo charged Petrol engines in passenger cars, vans or light commercial vehicles.

ADVANTAGES:

- Protection against sludge and deposits.
- Resists viscosity and thermal breakdown even in severe service.
- Very high resistance against oxidation.
- Viscosity grade suitable for most climates.
- Recommended for Petrol, LPG and E10 fuelled engines.
- Low loss by evaporation.

SPECIFICATIONS:

- SAE 10W30
- API SM
- ILSAC GF-3

APPLICATIONS:

Suitable for late generation naturally aspirated and turbo Petrol engines in passenger cars, vans or light commercial vehicles that recommend a GF-3 SAE 10W30 and API SM, SL or SJ motor oil.

TYPICAL CHARACTERISTICS:

Appearance		Amber
SAE Grade		10W30
Density 15°C	kg/L	0.865
Viscosity at 40°C	cSt	75
Viscosity at 100°C	cSt	10.9
Cold Cranking Viscosity VI		135

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.