



## SELECT 10W30 SM / CF GF-4 – ENGINE OIL

### PART NUMBERS:

1 Litre	88900941
5 Litre	88900942
6 Litre	92148132
20 Litre	88900943
205 Litre	88900944

### MOTOR OIL FOR PETROL AND DIESEL ENGINES

#### DESCRIPTION:

ACDelco Select SAE 10W-30 Motor Oil is a high quality mineral motor oil, suitable for use in 4-stroke naturally aspirated and turbo charged Petrol and Diesel engines in passenger cars, vans or light commercial vehicles.

#### ADVANTAGES:

- Protection against sludge and deposits.
- Resists viscosity and thermal breakdown even in severe service.
- Very high resistance against oxidation.
- Viscosity grade suitable for most climates.
- Recommended for Petrol, LPG and E10 fuelled engines.
- Low loss by evaporation.

#### SPECIFICATIONS:

- SAE 10W30
- API SM / CF
- ILSAC GF-4

#### APPLICATIONS:

Suitable for late generation naturally aspirated and turbo Petrol and Diesel engines in passenger cars, vans or light commercial vehicles that recommend a GF-4 SAE 10W30 and API SM, SL or CF SJ motor oil.

#### TYPICAL CHARACTERISTICS:

Appearance		Amber
SAE Grade		10W30
Density 15°C	kg/L	0.865
Viscosity at 40°C	cSt	75
Viscosity at 100°C	cSt	10.9
Cold Cranking Viscosity VI		135

*We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.*