



# SUPREME 10W30

## SM – ENGINE OIL

### PART NUMBERS:

1 Litre	89063552
5 Litre	89063553
20 Litre	89063554
205 Litre	89063555

### PREMIUM SEMI-SYNTHETIC MOTOR OIL FOR PETROL AND LPG ENGINES

### DESCRIPTION:

ACDelco Supreme 10W30 is a high performance semi-synthetic engine oil for naturally aspirated and turbocharged Petrol and LPG engines in passenger cars and light commercial vehicles.

### ADVANTAGES:

- Maintains its wear protection and fuel economy characteristics even in the most severe conditions.
- Resists oxidation and thermal breakdown even in severe service.
- Recommended for Petrol, LPG and E10 fuelled engines.
- Protection against sludge and deposits.
- Maintains viscosity grade.

### SPECIFICATIONS:

- SAE 10W30
- API SM
- ILSAC GF-4

### BENEFITS:

Can provide for the rationalisation of grades and containers in the workshop.  
Miscible with all mineral oil and synthetic oil, therefore no flushing is required.

### APPLICATION:

ACDelco Supreme 10W30 semi-synthetic can be used if the following SAE grades are specified in mineral oil: 5W40, 10W40, 15W40, 20W40, 20W30, 10W30, 5W30.

- *NB - In order to obtain the full benefits of ACDelco Supreme 10W30 please drain the system fully, replace filters, and refill with ACDelco Supreme 10W30.*

### TYPICAL CHARACTERISTICS

Property	Unit	Value	Test Method
SAE Grade		10W30	SAE J300
Kinematic Viscosity @ 40 °C	cSt	70 TYP	ASTM D445
Kinematic Viscosity @ 100 °C	cSt	10.9	ASTM D445
Viscosity Index		140	ASTM D2270
Pour Point	°C	-39	FLTP* 124
Specific Gravity @ 15 °C	Kg/L	0.87	
Flash Point, COC	°C	210 min.	ASTM D92
Total Base No.	mg KOH/g	9.7	ASTM D974
Sulfated Ash	% w/w	1.2	ASTM D874

*We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.*