



SELECT 15W40 SM / CF – ENGINE OIL

PART NUMBERS:

1 Litre	88900930
5 Litre	88900931
20 Litre	88900932
205 Litre	88900933

UNIVERSAL MOTOR OIL FOR PETROL AND DIESEL ENGINES

DESCRIPTION:

ACDelco Select 15W40 is a universal mineral motor oil, suitable for naturally aspirated and turbo charged Petrol and light Diesel engines.

ADVANTAGES:

- Very high resistance against oxidation.
- High detergent and dispersing properties.
- High performance in high and low temperature conditions.
- Excellent protection against wear.
- Recommended for Petrol, light Diesel, LPG and E10 fuelled engines.
- Very large application field.
- Low loss by evaporation.

SPECIFICATIONS:

- SAE 15W40
- API SM / CF
- ACEA A3 / B3

APPROVALS AND PERFORMANCE:

- Mercedes-Benz MB229.1

APPLICATIONS:

ACDelco Select 15W40 is a universal motor oil, which meets the strict ACEA A3 and B3 specifications as required by many late model European and Japanese Petrol and Diesel engines.

This oil is especially recommended for mixed fleets (passenger cars and light commercial vehicles). Designed to operate in the arduous Australian and New Zealand conditions.

TYPICAL CHARACTERISTICS:

SAE Grade	J300		15W40
Specific Gravity		kg/L	0.885
Viscosity at 40° C	ASTM D 445	cSt	105
Viscosity at 100° C	ASTM D 445	cSt	13.8
Viscosity index	ASTM D 2270		128

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.