

ACDelco Gear Oil



General Description				
75W-85	75W-90	85W-140	LS 80W-90	LS 140
ACDelco 75W85 Gear oil is a semi-synthetic, multipurpose, gear oil suitable for Modern Transmissions requiring a lower viscosity.	ACDelco 75W-90 Gear oil is a semi-synthetic, multipurpose, automotive gear oil with outstanding high temperature stability and performance and excellent low temperature fluidity, particularly suited to modern five speed manual gearboxes.	ACDelco Select SAE 85W-140 is a hypoid gear oil for highly stressed differentials and manual gearboxes As well as other crown wheel & pinion gears, steering mechanisms and distributor drives in vehicles and industrial machinery.	Limited Slip Hypoid Gear oil for highly stressed normal and limited slip differentials in passenger cars, light & heavy commercial vehicles as well as Agricultural and construction equipment	ACDelco Select SAE LS140 is an all season , high performance LS hypoid gear oil for highly stressed normal and limited slip differentials in passenger cars, light & heavy commercial vehicles as well as agricultural and construction equipment.

Advantages				
75W-85	75W-90	85W-140	LS 80W-90	LS 140
<p>Can be used where mineral oil an SAE 75W-85 is required.</p> <p>Suitable for use where API MT-1 lubricants are unsuitable.</p> <p>Compatible with many elastomers and other sealant materials.</p> <p>Longer life – increased oil change intervals.</p> <p>Mixes with mineral gear oils.</p> <p>Outstanding protection against wear. The lubricating film remains stable under very high loads and foaming is minimal at high speeds.</p> <p>Protects all metals normally found in gearboxes against corrosion and does not leave deposits on oil seals.</p>	<p>Rationalisation of grades - can be used when SAE 80W-90, SAE 80 and SAE 90 viscosity grades are specified.</p> <p>Easier cold-start gear changes.</p> <p>High resistance to oxidation.</p> <p>Mixes with mineral gear oils.</p> <p>Compatible with all elastomers and other sealing materials.</p>	<p>Good low temperature behaviour.</p> <p>Remains in grade even when subjected to heavy loads.</p> <p>The lubricating film remains stable under very high loads.</p> <p>Foaming is minimal at high speeds.</p> <p>Compatible with all elastomers & other sealing materials.</p> <p>Outstanding protection against wear.</p>	<p>All Season High Performance LS Hypoid gear oil.</p> <p>Very good viscosity retention behaviour even in severe conditions.</p> <p>The lubricating film remains stable under very high loads.</p> <p>Foaming is minimal at high speeds.</p> <p>Compatible with all elastomers & other sealing materials.</p> <p>Protects all metals normally found in gearboxes against corrosion and does not leave deposits on oil seals.</p> <p>Long Life.</p>	<p>All Season High Performance LS Hypoid gear oil.</p> <p>Very good viscosity retention behaviour even in severe conditions.</p> <p>The lubricating film remains stable under very high loads.</p> <p>Foaming is minimal at high speeds.</p> <p>Compatible with all elastomers & other sealing materials.</p> <p>Protects all metals normally found in gearboxes against corrosion and does not leave deposits on oil seals.</p> <p>Long Life.</p>

ACDelco offers a comprehensive Product Range to suit Most Makes & Models.

For your nearest ACDelco Automotive Parts Stockist call 1800 ACDelco

1800 ACDelco
acdelco.com.au



ACDelco Gear Oil



5 Litre

20 Litre

Application				
75W-85	75W-90	85W-140	LS 80W-90	LS 140
Syncromesh gearboxes.	Manual gearboxes.	Non Limited lip differentials.	Limited slip hypoid differentials.	Limited slip hypoid differentials.

Specifications				
75W-85	75W-90	85W-140	LS 80W-90	LS 140
API-GL4	API GL-5	API GL4/GL5	API GL-5/GL-5 LS	API GL5/GL5LS

Part Numbers				
75W-85	75W-90	85W-140	LS 80W-90	LS 140
5 Litre - 19104981	5 Litre - 19280528		5 Litre - 19280529	5 Litre - 19280531
20 Litre - 19104982	20 Litre - 89021798	20 Litre - 89021799	20 Litre - 19280530	20 Litre - 89021801

For further details refer to the ACDelco website www.acdelco.com.au

Available From:

1800 ACDelco
acdelco.com.au

