



ACDELCO CAR CARE CHEMICALS

CRANKCASE CLEANER (ENGINE FLUSH)

PART# 88901044

APPLICATION

Varnish, sludge and thickened engine oil in the crankcase and lubrication system can result in sticking hydraulic lifters, restricted lubricant supply, partial seizure between piston and cylinder walls, crankshaft and camshaft journals and bearings. This may result in cranking overload, scoring or total seizure of the engine.

PERFORMANCE

- will thin thickened oil
- will remove sludge and varnish build-up throughout the lubrication system so that it can be drained with the used oil
- contains a proven antiwear and extreme pressure additive to protect critical bearing areas and cylinder walls during flushing process

APPLICATION

Add entire content of the container to the engine oil just before draining. If the dipstick shows full, sufficient oil should be removed. Allow the engine to run at idle for 20-30 minutes. Drain the crankcase of oil, replace the oil filter and recharge the crankcase with new motor oil as recommended by the manufacturer.

CHARACTERISTICS

A proprietary blend of solvents, detergents, dispersants and penetrants that will effectively remove oil contaminants from the internal combustion engine.

Specific Gravity, @ 15°C:	1.016
Physical State:	Liquid
Flash Point (TOC):	30°C
NFPA Flammability:	Combustible Liquid Class II
VOC (% w/w):	49
OEM Approved	

PACKAGING MOST OFTEN SPECIFIED

350 ml bottle

PRECAUTIONS

Flammable liquid. Keep away from open flame or spark. Store in a cool, well ventilated area. Avoid inhalation of vapors. Avoid contact with eyes and skin. Wash thoroughly after handling. See Material Safety Data Sheet for further information.