



AUTOMATIC TRANSMISSION FLUID - ATF-III

DESCRIPTION.

ACDelco ATF III is a premium quality automatic transmission fluid for use in both passenger cars and light trucks requiring application of a DEXRON[®]-III (H) or MERCON[®] automatic transmission fluids. *ACDelco ATF III* is a high viscosity index product that offers superior oxidation stability, excellent cycling durability, good corrosion prevention, foaming resistance, and controlled frictional properties. This fluid also provides good seal compatibility; wear protection, and smoother shifting. The *ACDelco ATF III* fluid is not recommended for use in applications requiring a General Motors DEXRON[®]-VI Fluid.

ADVANTAGES.

- Superior oxidation stability, excellent cycling durability, good corrosion prevention, foaming resistance, and controlled frictional properties
- This fluid also provides good seal compatibility; wear protection, and smoother shifting

APPLICATIONS.

- *ACDelco ATF III* is recommended for application in General Motors vehicle transmissions requiring an DEXRON[®]-III (H), DEXRON[®]-III, DEXRON[®]-IIE, DEXRON[®]-II, and DEXRON[®] automatic transmission fluids.
- *ACDelco ATF III* is also recommended for use in power steering units as well as Allison transmissions or other torque converters requiring an Allison C-4 or Allison C-3 fluid.
- The *ACDelco ATF III* fluid is not recommended for use in applications requiring a General Motors DEXRON[®]-VI Fluid.

TYPICAL CHARACTERISTICS.

Appearance		Red
Gravity, API	D 4052	32.7
Flash, COC, °C (°F)	D 92	209 (408)
Pour Point, °C (°F)	D 5950	-51 (-60)
Viscosity	D 445	
cST at 40°C (SUS)		35.84 (175.0)
cSt at 100°C (SUS)		7.33 (50.7)
cP at -40°C		17,430
Viscosity Index	D 2270	176