



SELECT PLUS SEMI SYNTHETIC 75W-90

PART NUMBER:

5 Litre 19280528

20 Litre 89021798

60 Litre 19347434

SEMI SYNTHETIC GEAR OIL FOR MANUAL GEAR BOXES

DESCRIPTION:

ACDelco 75W-90 Gear oil is a semi-synthetic, multipurpose, automotive gear oil with outstanding high temperature stability and performance and excellent low temperature fluidity, particularly suited to modern five speed manual gearboxes.

ADVANTAGES:

- Rationalisation of grades - can be used when SAE 80W-90, SAE 80 and SAE 90 viscosity grades are specified.
- Easier cold-start gear changes
- High resistance to oxidation
- Mixes with mineral gear oils
- Compatible with all elastomers and other sealing materials.

SPECIFICATIONS: (Meets or exceeds)

- SAE 75/90
- API- GL5

SUITABLE FOR USE WITH FOLLOWING SPECIFICATIONS:

- MAN 342M-2
- MERITOR 0-76A
- ZF TE ML-05A, 07A, 12 E, 16B, C & D, 17B, 19B
- MIL -L—2105D

BENEFITS:

ACDelco Semi Synthetic 75W-90 allows for the reduction of the number of Gear oils in the workshop. It's high resistance to oxidation mean that it is suitable to long life and increased oil change intervals.

It provides outstanding protection against wear. The lubricating film remains stable under very high loads and foaming is minimal at high speeds.

The oil protects all metals normally found in gearboxes against corrosion and does not leave deposits on oil seals.

TYPICAL CHARACTERISTICS:

Appearance	Amber
Pour Point °C	-40
Density @ 15°C, kg/L	0.889
Viscosity Index	185
Flashpoint, COC, °C	220
Kinematic Viscosity @ 100°C, cSt	16

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

July 2016