



## SELECT SAE 85W-140 GEAR OIL GL-4, GL-5

**PART NUMBER:**  
20 Litre 89021799

### GEAR OIL FOR NON LIMITED SLIP DIFFERENTIALS

#### DESCRIPTION:

ACDelco Select SAE 85W-140 is a hypoid gear oil for highly stressed differentials and manual gearboxes As well as other crown wheel & pinion gears, steering mechanisms and distributor drives in vehicles and industrial machinery.

#### ADVANTAGES:

- Good low temperature behaviour
- Remains in grade even when subjected to heavy loads
- The lubricating film remains stable under very high loads
- Foaming is minimal at high speeds
- Compatible with all elastomers & other sealing materials
- Outstanding protection against wear

#### SPECIFICATIONS: (Meets or Exceeds)

- API GL4/GL5
- SAE 85W140
- ZF TE-ML 05A
- ZF TE-ML 12E
- ZF TE-ML 16D
- ZF TE-ML 21A

#### SUITABLE FOR USE WITH FOLLOWING SPECIFICATIONS:

- MIL-L-2105 D
- VOLVO 97310

#### BENEFITS:

ACDelco Select SAE 85W-140 is miscible and compatible with conventional branded gear oils Good cold flow properties supports easy starting & shifting in the warm up period. It features improved lubrication and excellent protection against wear even during short distance winter use. Due to the significant shear stability , the oil remains within range for the full length of the service intervals, which means lower maintenance.

#### TYPICAL CHARACTERISTICS:

SAE Grade J300	85W-140
Viscosity at 40° C ASTM D 445 cSt	427
Viscosity at 100° C ASTM D 445 cSt	30.7
Viscosity index ASTM D 2270	98
Density @ 15° C Kg/L	0.908

*We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.*

*July 2016*