



## SELECT SAE LS 140 GEAR OIL GL-5, GL-5 LS

### PART NUMBER:

5 Litre 19280531

20 Litre 89021801

### GEAR OIL FOR LIMITED SLIP HYPOID DIFFERENTIALS

### DESCRIPTION:

ACDelco Select SAE LS140 is an all season , high performance LS hypoid gear oil for highly stressed normal and limited slip differentials in passenger cars, light & heavy commercial vehicles as well as agricultural and construction equipment

### ADVANTAGES:

- All Season High Performance LS Hypoid gear oil
- Very good viscosity retention behaviour even in severe conditions
- The lubricating film remains stable under very high loads
- Foaming is minimal at high speeds
- Compatible with all elastomers & other sealing materials
- Protects all metals normally found in gearboxes against corrosion and does not leave deposits on oil seals
- Long Life

### SPECIFICATIONS: (Meets or exceeds)

- API MT-1
- API GL5 / GL-5 LS
- SAE J2360

### SUITABLE FOR USE WITH FOLLOWING SPECIFICATIONS:

- MACK GO-J
- MERITOR 0-76A
- ZF TE ML-07A /ML08
- Mil-PRF-2105E

### BENEFITS:

ACDelco Select SAE LS140 offers high performance in limited slip & non limited slip applications. It offers outstanding protection against wear with no loss of performance. It provides for quieter running with no chattering and screeching. Due to its long life characteristics, it provides lower maintenance

### TYPICAL CHARACTERISTICS:

SAE Grade J300	85W-140
Viscosity at 40° C ASTM D 445 cSt	430
Viscosity at 100° C ASTM D 445 cSt	30
Viscosity index ASTM D 2270	95 min
Density @ 15° C Kg/L	0.910