



## Multi Vehicle Transmission Fluid Fully Synthetic DEXRON III A.T.F.

### PART NUMBER:

1 Litre 19315204  
5 Litre 19315205  
20 Litre 19315206  
60 Litre 19347437  
205 Litre 19315207

### PREMIUM SYNTHETIC, HIGH PERFORMANCE AUTOMATIC TRANSMISSION FLUID.

### DESCRIPTION:

Designed to meet the demanding requirements of many modern Japanese passenger vehicles, SUV's and light commercials. Multi-trans uses selected high quality base-stocks combined with a specially developed additive technology. This delivers a fluid which exceeds the performance of many original fluids. It has excellent anti-shudder-properties with a high friction-level constant over lifetime

### ADVANTAGES:

- Enhanced, long-term frictional properties.
- Outstanding film-strength and anti-wear properties
- Exceptional shear stability.
- Excellent low-temperature fluidity
- Exceptional thermal and oxidation stability
- Compatible with mineral ATF fluids and all common seal materials

### SPECIFICATIONS: (Meets or exceeds)

- JASO M315 TYPE 1A

### SUITABLE FOR USE WITH FOLLOWING SPECIFICATIONS:

- AISIN WARNER / AW-1
- DAEWOO
- FIAT TYPO T-IV
- HONDA ATF Z-I
- JWS 3309/TYP T-IV
- MAZDA ATF D-III/ATF M-3
- SAAB 3309
- TOYOTA TYPE D-2/WS
- BMW MINI 83 22 0 402 413 / 83 22 7 542 290
- DAIHATSU ALUMIX ATF MULTI
- FORD MERCON / M2C924-A / M2C922-A1/ 95LE
- HYUNDAI SP-III/IV
- JATCO 3100 PL085/ FWD (N402) / JF506E (K17)
- MITSUBISHI SP-II/III
- SUBARU ATF OIL/ATF OIL SPECIAL/ ATF HP
- TOYOTA TYPE T/T-II/T-III/T-IV
- CHRYSLER ATF +3 / +4
- DEXRON® III
- GM 9986195
- ISUZU BESCO ATF-II/ATF-III
- KIA SP-IV
- NISSAN C/D/J
- SUZUKI ATF 3309/3317
- VW G 052 990/055 025

### BENEFITS:

ACDelco Multi-trans has such wide ranging applications it can easily replace all D3 type fluid in the workshop. Its High Friction level and its excellent anti wear properties Helps to improve and extend transmission efficiency, smooth shifting performance and fuel economy. It does this even in extremely cold or hot temperatures

### TYPICAL CHARACTERISTICS:

Appearance	Clear Red Fluid
Specific gravity @15° C kg/L	0.849
Viscosity at 40°C ASTM D 445 cSt	40
Viscosity at 100° C ASTM D 445 cSt	7.2
Viscosity index ASTM D 2270	150
Pour Point, FLTP*	124 < -45 °C
Flash Point, COC ASTM D92	195 °C

*We reserve the right to alter the general characteristics of our products in order to let our customers have the benefit of the latest technical evolutions.*

July 2016