



SELECT SAE 10W-30 ENGINE OIL SN/CF ILSAC GF-5

PART NUMBER:

5 Litre 88900942
6 Litre 92148132
20 Litre 88900943
205 Litre 88900944

**ADVANCED MOTOR OIL FOR LATE GENERATION PETROL ENGINES
REQUIRING A LOW VISCOSITY OIL.**

DESCRIPTION:

ACDelco Select SAE10W-30 is specially formulated to meet the demands of late generation petrol engines. Formulated to increase service intervals, ACDelco Select SAE 10W30 will also aid in the reduction of fuel consumption whilst providing optimal protection against engine wear.

ADVANTAGES:

- Suitable for use where a GF-5 is specified.
- High Viscosity Index for increased engine circulation, providing improved fuel economy and increased engine wear protection.
- Excellent protection against wear due to stable lubricating film at full-throttle operation.
- Low volatility- Reducing oil consumption.
- Compatible with all engine seals and gaskets.

SPECIFICATIONS: (Meets or exceeds)

- SAE 10W-30
- API SN/CF
- ILSAC GF-5

BENEFITS:

ACDelco Select SAE10W-30 is a low viscosity Fuel economy mineral motor oil which meets the latest API specs and the strict ILSAC GF-5 as required by many late model European & Japanese engines. As well as delivering excellent fuel consumption results it is designed to protect against sludging, creating minimal engine deposits for cleaner engine protection.

Provides excellent start up performance and engine efficiency, especially for vehicles used in city and suburban driving conditions.

TYPICAL CHARACTERISTICS:

SAE Grade J300	10W-30
Specific gravity @15° C kg/L	0.865 Kg/L
Viscosity at 40° C ASTM D 445 cSt	75 cSt
Viscosity at 100° C ASTM D 445 cSt	10.9 cSt
Viscosity index ASTM D 2270	135

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

July 2016