



# SELECT PLUS SEMI SYNTHETIC 10W-40 SN/CF A3/B3,B4

## PART NUMBER:

5 Litre 19280517  
20 Litre 19280518  
205 Litre 19280519

## SELECT PLUS SEMI SYNTHETIC OIL FOR PETROL OR DIESEL ENGINES

### DESCRIPTION:

Synthetically enhanced engine oil for everyday & high performance engines, in passenger and light commercial vehicles. Suitable for vehicles using LPG, leaded and unleaded fuel, and many diesel engines. Meets the latest API specs and provides excellent fuel consumption results.

### ADVANTAGES:

- A stay-in-grade lubricant, which maintains its wear protection and fuel economy characteristics even in the most severe conditions.
- Superior performance when compared to API SM, SL and SJ lubricants, particularly in the areas of oil consumption, fuel economy, high temperature-deposit control and oxidation
- Low oil consumption due to minimum evaporative loss.
- Resists oxidation and thermal breakdown even in severe service.
- Protection against sludge and deposits.

### SPECIFICATIONS: (Meets or exceeds)

- SAE 10W40
- API SN/CF
- ACEA A3/B3,B4

### BENEFITS:

Rationalisation of grades - can be used if the following SAE grades are specified: SAE 5W-40, SAE 10W-40, SAE 15W-40, SAE20W-40.

No loss of performance as a result of unwanted deposits in cylinders, on pistons, valves, spark plugs and in turbochargers. Compatible with all gaskets and seals. Miscible with all mineral oil and synthetic oil. Therefore no flushing is required.

### TYPICAL CHARACTERISTICS:

SAE Grade J300	10W40
Specific gravity @15° C kg/L	0.86
Viscosity at 40° C ASTM D 445 cSt	100
Viscosity at 100° C ASTM D 445 cSt	14.5
Viscosity index ASTM D 2270	140

*We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.*

July 2016