



## SELECT FLEET HD DIESEL 15W-40 CI-4/SL E7/E3/E5

### PART NUMBER:

5 Litre 89063556

20 Litre 89063557

205 Litre 89063558

### SELECT FLEET HD DIESEL ENGINE OIL.

#### DESCRIPTION:

An all Fleet high performance engine oil for diesel engines with and without turbo charging in trucks, buses, construction, industrial machinery, pick-ups and vans. Select Fleet HD Diesel 15W40 is a breakthrough in diesel engine oil technology. Suitable for European, American and Japanese diesel engines operating under the most arduous conditions in both on and off highway applications. .

#### ADVANTAGES:

- Stay-in-grade quality, even under the most severe conditions.
- Prevents excessive viscosity increase due to high temperature oil oxidation,
- Proven bore polish protection.
- Longer drain intervals, less downtime. .
- Better maintenance of oil film for reduced wear and increased engine durability.
- Superior soot handling capabilities when compared to CH-4 lubricants.

#### SPECIFICATIONS: (Meets or exceeds)

- API CI-4/SL
- ACEA E7/E3/E5/
- CAT EFC1-a / ECF-2
- GLOBAL DHD-1
- CUMMINS CES 20076 / 20077 / 20078
- MACK EO-N
- MAN M 3575 -1
- MB 228.3,
- RENAULT RLD-2
- VOLVO VDS-3

#### SUITABLE FOR USE WITH FOLLOWING SPECIFICATIONS:

- ALLISON C-4
- CASE MS1121
- CAT TO-2
- CUMMINS CES 2007 1/2
- IVECO 18-1804 Classe T2 E7
- NH 33 H

#### BENEFITS:

High performance specifications in a single product will benefit both commercial fleet and plant operators where OEM's specify differing requirements. Ideal for mixed vehicles and machinery fleets which want to use one type of oil throughout the year. ESI (Extended Service Interval) capabilities of up to 30,000KM depending on application

#### TYPICAL CHARACTERISTICS:

|                     |              |                          |
|---------------------|--------------|--------------------------|
| Viscosity at 40° C  | DIN 51562-1  | 107.9 mm <sup>2</sup> /s |
| Viscosity at 100° C | DIN 51562-1  | 14.6 mm <sup>2</sup> /s  |
| Pour Point          | DIN ISO 3016 | -36 °C                   |
| Flash Point COC     | DIN ISO 2592 | 233 °C                   |
| Viscosity index     | DIN ISO 2909 | 137 N/A                  |
| Density @ 15° C     | DIN 51757    | 0.886 g/ml               |

*We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.*

July 2016