



SELECT SAE 15W-40 ENGINE OIL SN/CF ACEA A3/B3/B4

PART NUMBER:

5 Litre 88900931

20 Litre 88900932

205 Litre 88900933

UNIVERSAL MOTOR OIL FOR PETROL and DIESEL ENGINES

DESCRIPTION:

ACDelco Select SAE15W-40 is a universal mineral motor oil suitable for naturally aspirated and turbo charged Petrol & Diesel Engines

ADVANTAGES:

- Very High resistance against Oxidation
- High Detergent and dispersant properties
- High Performance in High and low temperature conditions.
- Excellent protection against wear.
- Recommended for Petrol, Light Diesel LPG & E10 Fuelled engines.
- Very large application field
- Low Loss by evaporation

SPECIFICATIONS: (Meets or exceeds)

- SAE 15W-40
- API SN/CF
- ACEA A3/B3/B4

BENEFITS:

ACDelco Select SAE15W-40 is a universal mineral motor oil which meets the latest API specs and the strict ACEA A3/B3/B4 specifications as required by many late model European & Japanese engines As well as delivering excellent fuel consumption results it is designed to operate in the arduous Australian and New Zealand driving conditions. This oil is especially recommended for mixed Fleets (Passenger cars & light commercial vehicles)

TYPICAL CHARACTERISTICS:

| | |
|------------------------------------|--------|
| SAE Grade J300 | 15W-40 |
| Specific gravity @15° C kg/L | 0.885 |
| Viscosity at 40° C ASTM D 445 cSt | 105 |
| Viscosity at 100° C ASTM D 445 cSt | 13.8 |
| Viscosity index ASTM D 2270 | 128 |

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

July 2016