



# PREMIUM EURO LONG LIFE SYNTHETIC 5W30 A3 / B4 – C3

## PART NUMBER:

20 Litre 19280520

205 Litre 19280521

## PREMIUM SYNTHETIC MOTOR OIL FOR PETROL & DIESEL ENGINES

### DESCRIPTION:

Premium Euro Long Life Synthetic 5W-30 is a Premium engine oil for use in passenger cars and vans over the full temperature range from very low up to very high temperatures. It fulfils all requirements of engine oils for vehicles fitted with exhaust gas after treatment devices. It is suitable for use in vehicles where the VW 504.00/507.00 specification is called for. Also the product can be applied in many vehicles of European or Asian manufacturers if the use of an ACEA C3 engine oil is specified.

### ADVANTAGES:

- Due to base oil blend, even further improved fuel economy of up to 1.7% compared to many engine oils of the same SAE-viscosity
- Protects exhaust gas after treatment systems
- Excellent wear protection with maximum power output
- Protection against sludge and deposits in engines & Turbochargers
- Applicable for diesel and petrol engines

### SPECIFICATIONS: (Meets or exceeds)

- ACEA C3
- ACEA A3/B4
- VW 504.00 / 507.00
- PORSCHE C30
- BMW LONGLIFE -04
- MB 229.51
- MB 229.31

### SUITABLE FOR USE WITH FOLLOWING SPECIFICATIONS:

- FORD M2C917-A
- FIAT 9.55535-S3

### BENEFITS:

Premium Long Life Euro 5W30 offers significant benefits in highly stressed or stop start engines. Oil circulation time at low temperatures is up to 55% faster and engine start time is improved by 35%. It offers benefits to all advanced, fuel efficient engines regardless of their emission category.

### TYPICAL CHARACTERISTICS:

SAE Grade J300	5W30
Flashpoint (COC) °C	210
Specific gravity @15° C kg/L	0.849
Viscosity at 40° C ASTM D 445 cSt	71.1
Viscosity at 100° C ASTM D 445 cSt	11.6
Viscosity index ASTM D 2270	155

*We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.*

July 2016