

## PREMIUM HP LONG LIFE SYNTHETIC 5W-40 SN/CF. ACEA C3

**PART NUMBER:** 

1 Litre 19350796 5 Litre 19350797 20 Litre 19350798 205 Litre 19350799

## PREMIUM HP LONG LIFE SYNTHETIC 5W40 MOTOR OIL DESCRIPTION:

Is a premium engine oil for passenger cars, SUV's and Light Commercial vehicles. The latest technology allows for maximum performance from very low to very high temperatures This product is also formulated to be used in vehicles with exhaust gas after treatment systems such as catalysts or particulate filters.

Δ	ח	V	Δ	N	T/	١G	F	S	
м	ப	v	н	w		417	_		

☐ Designed to fulfil the viscosity requirements of Series 1 Holden Captiva, Epica or Cruze Diesel.
□ Protects exhaust gas after treatment systems
☐ Excellent wear protection with maximum power output
□ Protection against sludge and deposits in engines & Turbochargers
□ Applicable for diesel and petrol engines.
APPROVALS:
□ GM dexos 2™
SPECIFICATIONS: (Meets or exceeds)
□ ACEA C3
□ API SN/CF
SUITABLE FOR USE WITH FOLLOWING SPECIFICATIONS:
□ ACEA A1/B1, A5/B5, A3/B4
□ MB 229.31
□ RENAULT RN0700/RN07010
□ PORSCHE A40
□ BMW LL 04
UW 502.00/ 505.00/ 505.01

## **BENEFITS:**

Premium HP Long Life Synthetic SAE 5W-40 fulfils engine oil requirements for vehicles requiring dexos 2™, API SN or ACEA C3 specifications with a higher viscosity. It also offers significant benefits including extended service intervals for some vehicles. The oil assists in preventing deposits in the engine and turbocharger to ensure full boost pressure, engine power and fuel economy are maintained.

## **TYPICAL CHARACTERISTICS:**

SAE Grade J300	5W40
Flashpoint (COC) °C	250
Viscosity at 40° C ASTM D 445 cSt	85
Viscosity at 100° C ASTM D 445 cSt	14.2
	0400 (

Dynamic Viscosity mPas 6100 (-30° C)

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

June 2017